

HIGH INTENSITY STROBE LIGHT (WHITE)

(HIGH-W120)



FEATURES

- Light weight fiberglass flash head (also available in S.S.)
- Tempered glass lens – no aging discoloration
- Up to 10 controllers available in a single enclosure
- Only one cable is needed to supply 3 flash heads

SPECIFICATIONS

Light output

Flash color	White
Intensity, day mode	270 000 cd \pm 25%.
Intensity, twilight mode	20 000 cd \pm 25%.
Intensity, night mode	2 000 cd \pm 25%.
Horizontal coverage	120°
Vertical beam	3°
Expected min. lamp life	40 000 hours

Electrical value

Power consumption	235 Watts
Current (120Vac version)	4 A (rms)
Power requirements	120 Vac 50/60hz also available in 240 Vac

Mechanical

Flash head weight	Fiberglass : 11.8 Kg (26 lbs) Stainless steel : 14 Kg (31 lbs)
Controller weight	15 Kg (33 lbs)
Flash head dimensions (W x H x D)	430 mm x 380 mm x 180 mm (17" x 15" x 7")
Controller dimensions (W x H x D)	355 mm x 406 mm x 222 mm (14" x 16" x 8¾")

Others

FAA type	L-856, L-857
Transport Canada type	CL-856, CL-857
Operating temperature	-55°C to 55°C (-67° F to 131°F)
Warranty	2 years

ETL CERTIFIED FOR FAA:

- AC 150/5345-43F

COMPLIANT WITH:

-  SPE-1000

-  Transports Canada Transport Canada Standard 621