

LED Hybrid Beacon (White & Red)

LED-B-HYBRID



FEATURES

- Reduced energy consumption by 90% versus incandescent
- Optical design to reduce ground disturbance
- 10 year durability
- Very stable light output under voltage variations
- Standard 13 1/4" bolt circle
- Controller and power supply are located in a separate box, outside the light unit.

SPECIFICATIONS

Light output

| | |
|-------------------------|-----------------------------|
| Lamp type | LED |
| Light color | White and red |
| Effective intensity | 20K day, 2K night cd; ±25%. |
| Horizontal coverage | 360° |
| Vertical beam | 3° |
| Expected min. lamp life | 10 years + |

Electrical value

| | |
|--------------------|-----------------------|
| Power consumption | 60 W day / 20 W night |
| Power requirements | 120/240 Vac 50/60hz |

Mechanical

| | |
|--|--|
| Beacon weight | 11 Kg (24 lbs) |
| Beacon dimensions (dia. x height) | 48,1 cm x 35.5 cm (19" x 14") |
| Controller weight | 11.3 Kg (25 lbs) |
| Controller dimensions (width x height x depth) | 381mm x 444mm x 211mm (15" x 17.5" x 8.3") |


Others

| | |
|---------------------------|--------------------------------|
| FAA type | L-865 / L-864 |
| Transport Canada type | CL-865 / CL-864 |
| Configurable for Catenary | L-866-885 / CL-866-885 |
| Operating temperature | -40°C to 55°C (-40°F to 131°F) |
| Warranty | 5 years |

ETL CERTIFIED FOR FAA:

- AC 150/5345-43G

COMPLIANT WITH:

-  Transports Canada Standard 621
-  Transport Canada Standard 621