



Never alone in the dark.

RED LIGHT CONTROL/MONITORING SYSTEM

TS-950



FEATURES

- Beacon and steady burning obstruction light control
- Very stable under voltage variations
- "0" voltage switching reduces noise and preserves bulb life (2 to 3 times longer lamp life)
- Heatsink mounted outside the enclosure for proper heat dissipation
- Automatic photo control
- Extremely reliable
- Transfer function: turns on only one bulb of a DOL fixture and transfers to the other bulb in case of a failure of the first one.
- 3 alarm contacts for remote diagnostics of lamps and controller

SPECIFICATIONS

Monitoring

Lamp type	LED or incandescent.
-----------	----------------------

Electrical value

Power consumption	5 Watts
Power requirements	120 Vac 50/60hz also available in 240 Vac or 24 Vdc

Mechanical

Weight	3,6 Kg (8 lbs.)
Dimensions (W x H x D)	241 mm x 292 mm x 140 mm (9½" x 11½" x 5½")
Enclosure material	Fiberglass

Others

Enclosure rating	Nema 1
Operating temperature	-40°C to 55°C (-40°F to 131°F)
Warranty	2 years

COMPLIANT:

- SPE-1000
- Transports Canada / Transport Canada Standard 621
- Industry Canada / Industrie Canada ICES-003
- PART 15