



Never alone in the dark.

# LIDS LIGHTING MANAGER

Windfarm Obstruction Lights - Monitoring System for use with Lighting Intensity Dimming Solution (LIDSCPUKIT)



## FEATURES

- Automated obstruction light control and monitoring system
- Map display with color coded status
- Manual radar bypass switch
- Manual control – All beacons as a group or per beacon
- Detailed and summary event logs
- LIDS support (Lighting Intensity Dimming Solution)
- MODBUS, SNMP and dry contact interfaces
- Static or Dynamic IP addressing
- 2x 1GB network interfaces
- 1U 19" Rackmount industrial computer
- 1U 19" Rackmount 17" 1280x1024 KVM



## SPECIFICATIONS

Power Input Rating	Computer: 100-240V 50/60hz 3A KVM: 100-240V 50/60hz 1A
Weight	Computer: 10 lbs (4.5 Kg) KVM: 26 lbs (11.8 Kg)
Dimensions	Computer: 11 x 19.1 x 1.75 in 28 x 48.5 x 4.4 cm KVM: 21 x 19.1 x 1.75 in 54 x 48.5 x 4.4 cm
Compliance	Computer: UL, CE, RoHS, FCC KVM : CE, RoHS, FCC
Operating temperature	0°C to 40°C (0°F to 104°F)
Warranty	5 years



# Dim the light